

Zebra® G-Series™ printers



Making a difference to your desktop

Zebra's G-Series compact desktop printers deliver best-in-class speed and performance for print widths up to 104mm (4"). From the basic GK™ model to the feature-rich GX™ model, the G-Series printers offer a reliable, durable and flexible desktop solution for any printing application and budget.

Built with Zebra durability and reliability, the G-Series GK model provides the best value of all basic desktop thermal printers, while the premier GX model supports a variety of industries and applications with the widest range of features. Choose the space-saving direct-thermal version of either model for the smallest footprint of any 104mm (4") desktop printer, or the direct-thermal/thermal-transfer version to save users time with the easiest ribbon-loading system available.

With both EPL™ and ZPL® native on all models and a variety of connectivity options for personal, local and networked systems, the G-Series printers integrate easily and seamlessly with other Zebra printing solutions.

www.g-series.info

Zebra's G-Series printers support many applications, including:

- **Healthcare:**
 - Patient identification
 - Sample and specimen identification
 - Sterile services labelling
 - Pharmacy prescription labelling
- **Retail:**
 - Product labelling
 - Price mark-down
 - Shelf-edge labelling
 - Voucher and receipt printing
- **Travel:**
 - Boarding passes
 - Bag tags
- **Hospitality, Service & Leisure:**
 - Event and exhibition ticketing
 - Fast-food labelling
 - Gaming and betting slips
- **Supply chain:**
 - Process, product and shipping labelling
- **Post & parcel:**
 - Electronic franking
 - Address labelling

Get the most out of your Zebra, put genuine Zebra™ supplies in!

Zebra offers a wide range of supplies for G-Series printers, all made to a high standard and suitable for a variety of applications.

- Manufactured exclusively for Zebra printers
- Laboratory-tested for optimum performance
- Proven to minimise wear and tear on printheads



▶ For more information, visit www.zebra.com

SPECIFICATIONS AT A GLANCE*

STANDARD FEATURES

- Print methods: Direct thermal or thermal transfer
- Programming languages: EPL and ZPL as standard
- Construction: Dual-wall frame
- Tool-less replacement of printhead and platen
- OpenACCESS™ for easy media loading
- Quick and easy ribbon loading
- Auto-calibration of media

PRINTER SPECIFICATIONS

Resolution

- 8 dots per mm/203dpi
- 12 dots per mm/300dpi (optional GX430t™)

Memory

- Standard: 4MB flash; 8MB SDRAM
- Optional: 8MB (12MB total) flash with RTC (GX models)

Print width

- 104mm/4.09"

Maximum print length

- 990mm/39.0"

Maximum print speed

- GK420: 127mm/5" per second
- GX420: 152mm/6" per second
- GX430: 102mm/4" per second

Media sensors

- Standard: Fixed reflective and transmissive sensors
- Adjustable reflective and multi-position transmissive sensor (GX models)

MEDIA CHARACTERISTICS

Maximum label and liner length

- Maximum non-continuous: 990mm/39"

Maximum label and liner width

- 19mm/0.75" to 108mm/4.25"

Maximum media roll size

- 127mm/5" O.D.

Media thickness

- 0.076mm/0.003" to 0.19mm/0.0075"

Media types

- Roll-fed or fanfold, die-cut or continuous direct-thermal labels with or without black mark, tag stock, continuous receipt paper, wristbands

RIBBON CHARACTERISTICS

Outside diameter

- 35mm/1.36"

Length

- 74m/244' (when using 0.08mm ribbon thickness)

Ratio

- 1:1 media roll to ribbon

Width

- 33.8mm/1.33" to 109.2mm/4.3"

Core inner diameter

- 12.7mm/0.5"

OPERATING CHARACTERISTICS

Environmental

- Operating temperature: 4.4°C to 41°C

- Storage temperature: -40°C to 60°C
- Operating humidity: 5% to 95% non-condensing
- Storage humidity: 5% to 95% non-condensing

Electrical

- Auto-detectable (PFC-compliant) 100–240VAC, 50–60Hz

Agency Approvals

- Emissions: FCC Part 15, Subpart B, VCCI, C-Tick
- Emissions and Susceptibility: (CE): EN 55022 Class B, EN 61000-3-2, EN 61000-3-0 and EN 55024, CCC
- Safety: CB Scheme IEC 60950:1991 +A1 +A2 +A3 +A4, TÜV NRTL, IRAM NOM, AAMI, CCC

PHYSICAL CHARACTERISTICS

Width

- Direct thermal 171mm/6.75"
- Thermal transfer 193mm/7.6"

Height

- Direct thermal 152mm/6.0"
- Thermal transfer 190mm/7.5"

Depth

- Direct thermal 210mm/8.25"
- Thermal transfer 254mm/10.0"

Weight

- Direct thermal 1.4kg/3lb
- Thermal transfer 2.1kg/4.6lb

ZEBRALINK™ SOLUTIONS

Software

- ZebraDesigner Driver (downloadable from www.zebra.com)
- ZebraDesigner™ Pro
- ZebraDesigner
- ZebraNet™ Bridge Enterprise
- ZebraNet Utilities v7.0
- Zebra Universal Driver

Networking/Connectivity

- ZebraNet® 10/100 Print Server (optional)
- 802.11g wireless LAN (optional)
- Bluetooth® wireless PAN (optional)

Firmware

- EPL2™
- EPL Line Mode (Direct thermal only – GK420d and GX420d)
- ZPL II®
- Web View
- Alert

COMMUNICATION AND INTERFACE CAPABILITIES

GX models have triple interface standard

- RS-232 serial interface, DB-9
- USB 1.1, bi-directional
- Parallel DB-25 female connector, bi-directional
- ZebraNet 10/100 Print Server (optional) – replaces parallel
- 802.11g wireless (optional)
- Bluetooth wireless (optional)
- Wireless options include LCD for visual communication

GK models have dual interface standard

- RS-232 serial interface, DB-9
- USB 1.1, bi-directional
- ZebraNet 10/100 Print Server (optional) – replaces serial

FONTS/GRAPHICS/SYMBOLOLOGIES

Fonts and character sets

- 16 resident expandable ZPL II bitmap fonts
- One resident scalable ZPL font
- Five resident expandable EPL2 fonts
- Native OpenType™ font support
- Unicode™-compliant for multi-language applications

Graphics features

- Supports user-defined fonts and graphics including custom logos
- ZPL II drawing commands for boxes and lines

Bar code symbolologies

- Bar code ratios: 2:1 (non-rotated) and 3:1 For EPL and ZPL except where noted
- Linear Bar Codes: Codabar, Code 11 (ZPL), Code 39, Code 93, Code 128, EAN-8, EAN-13, EAN-14 (ZPL), German Post Code (EPL), GS1 DataBar (RSS), Industrial 2-of-5 (ZPL), Interleaved 2-of-5, ISBT-128 (ZPL), Japanese Postnet (EPL), Logmars (ZPL), MSI, Plessey, Postnet, Standard 2-of-5 (ZPL), UCC/EAN-128 (EPL), UPC-A, UPC-A and UPC-E with EAN 2 or 5 digit extensions, UPC-E, UPC and EAN 2 or 5 digit extensions (ZPL)
- Two-dimensional: Codablock (ZPL), Code 49 (ZPL), Data Matrix, (ZPL), MaxiCode, MicroPDF417, PDF417, QR Code

OPTIONS AND ACCESSORIES

- Label dispenser with label-present sensor
- ZebraNet 10/100 Print Server – internal Ethernet for network communication and printing
- 802.11g wireless (optional)
- Bluetooth wireless (optional)
- Wireless options include LCD for visual communication
- Adjustable media sensor (GX models)
- Cutter for various media types (GX models)
- 300dpi print resolution printing for fine detail and crisp images (GX430t)
- 8MB flash memory with real-time clock for total of 12MB (GX models)
- Font packs – Asian and other international font kits
- KDU Plus™ and KDU™ keyboard display units for standalone printing solutions

*Specifications subject to change without notice.

©2008 ZIH Corp. EPL, EPL2, genuine Zebra, KDU Plus, OpenACCESS, ZebraDesigner, ZebraLink, ZebraNet and all product names and numbers are Zebra trademarks, and Zebra, representation of Zebra Head, ZebraNet, ZPL and ZPL II are registered trademarks of ZIH Corp. All rights reserved. Bluetooth is a registered trademark of the Bluetooth SIG, Inc. OpenType is either a registered trademark or a trademark of Microsoft Corporation in the United States and/or other countries. Unicode is a trademark of Unicode, Inc. All other trademarks are the property of their respective owners.

Thinking about mobilising your workforce?

The use of mobile printers in a warehouse or supply-chain environment improves productivity and provides a fast return on investment.

- ▶ To find out how your business could benefit from a Zebra mobile-printing solution, please visit www.zebra.com, call +44 (0)1494 472872 or e-mail mseurope@zebra.com



Zebra Technologies – EMEA Headquarters

E-mail: mseurope@zebra.com

Other EMEA Locations

Europe: France, Germany, Italy, the Netherlands, Poland, Spain, Sweden Middle East, Africa & India: Dubai, India, South Africa