

## Beam Scale LW-BSE

High capacity beam scale with accurate weighing up to 3500kg. Surface electroplated. Often used to weigh long goods or conveyor. Height only 75 mm



Standard indicator

- ✓ 2 pcs Beams, each dimension 1 250 x 130 mm.
- ✓ Very robust steel construction, with electroplated surface treatment.
- ✓ Capacity max 3500 kg
- ✓ Very low, only 75 mm height.
- ✓ Designed with four load cells of steel, nickel-plated with protection IP-67.
- ✓ Combined lifting handle and cable protection.
- ✓ Designed to not be damaged by chock loads.
- ✓ Load cell support to the floor is feet with rubber surface.

# LI-101 Indicator Specifications:

## Display specification:

Display type:	LCD display with LED backlight. 6 digits, height 25,4 x 10 mm.
Display ( functions by setup ):	Peak Hold function.
	Zero recall function.
	Weight accumulation.
	Animal mode with different filter levels.
	Tare and Preset Tare function.
	Wall mount bracket.
Keys:	ON/OFF, Zero, Tare, Gross/Net, F2, F1/HR, Enter
Indicator marks:	Zero, Tare, Motion, M+, Gross, Pre-Tare, Range 1, Range 2,
Option I/F:	RS-232 / RS-485: 9 pin D-sub including RTC function.

## Power requirement:

Adapter specification:	Input: 120/230V AC 50 ~ 60Hz. Output: 9V / 1000mA.
Standard battery:	6V Ni-MH / 1800mAh, rechargeable battery kit.
Power consumption:	120mA (4 load cells + backlight + RS-232) = 15 hours.

## General:

Operating temperature:	0°C to 40°C.
Operating humidity:	< 85%RH Max. (Non-condensing).
Net weight:	33 kg ( including indicator ).