



SHC

PRODUCT INFORMATION

- ✓ 24 bit high speed A/D converter with 1,000,000 internal count
- ✓ 1/30000 high-resolution single interval for SHC
- ✓ Designed to meet industrial high precision counting applications
- ✓ Protection devices against overload and shock
- ✓ Power-ON Zero Tracking, Digital Motion Filter at Zero and weighing, Smart Power Saving, Auto Piece Weight Enhancement, Auto Calibration and Accumulation Functions, Low Battery Warning Signal
- ✓ Full tare range (subtractive)
- ✓ Completed with Full Numeric Keypad, Over Weight and Quantity Alarm, 99 PLU memory and 6 quick PLU memory, 8 x One-Touch piece Weight and Sample Size Warning and Charging Status Indicator
- ✓ Bold type wide angle LCD display
- ✓ Dual power sources: by built-in rechargeable battery or power adaptor
- ✓ Adjustable feet, backlight, bubble level and power adaptor
- ✓ Long battery operation time: 100 hours plus
- ✓ Options available: RS-232 Interface



MODEL	CAPACITY	READABILITY	PLATFORMSIZE
SHC-3	3 kg	0.1 g	180 x 292 mm
SHC-6	6 kg	0.2 g	230 x 345 mm
SHC-15	15 kg	0.5 g	230 x 345 mm
SHC-30	30 kg	1 g	230 x 345 mm
SHC-60	60 kg	2 g	230 x 345 mm

